

COMPONENTS 2005

(PTY) LTD

t/a ENGINE & HEAVY DUTY COMPONENTS

HEAD OFFICE JOHANNESBURG

Tel: +27 (0)11 870 5000
Fax to Mail: 086 676 6628
Cnr Hubert & Marshall Streets,
Marshalltown, Johannesburg 2001
PO Box 6541 Johannesburg, 2000,
South Africa
ehd@ehd.co.za

BLOEMFONTEIN

Tel: +27 (0)51 430 5404 17 Krause Street, Oranjesig PO Box 12471, Brandhof, 9324 South Africa ehdbloem@ehd.co.za

CAPE TOWN

Tel: +27 (0)21 510 0567 25 Bellray Business Park Ampere Street, Stikland Industrial Cape Town, 7530 PO Box 1037, Milnerton, 7435 South Africa ehdcapetown@ehd.co.za

DURBAN

Tel: +27 (0)31 700 1160 Unit 3,Hillmax 31 Hillclimb Rd,Westmead 3610 PO Box 1054 Nagina 3604, South Africa ehd.dbn@ehd.co.za

GAF1M2

Madal



Model	GAF - 1M 2Kw
Rated sea-level power @ 1500 RPM	2.6 kW (3.4866 HP)
Derated power at 1500m ASL @ 1500 RPM	2.0 kW (2.682 Hp)
Permissible working range	1.2 - 2.2 kW(1.6092 - 2.9502 Hp)
Number of Cylinders	One
Bore / Stroke	80.00mm X 110.00mm
No. of strokes	Four
Type of Cooling	Air Cooling
Maximum Ambient Temperature for specified performance	45 C
Half speed PTO Shaft + rpm (Yes / No)	Yes (750RPM)
Rotation of PTO Shaft (clockwise / anti-clockwise)	Clockwise seeing from flywheel
PTO Shaft suitable for V-belt drive (Yes / No)	Yes
Diameter and lenght of shaft + Stub shaft	35.0 mm Length 150 mm
Type of oil filter fitted	Cartridge Type
Type of air cleaner fitted	Dry Type
Type of fuel filter fitted	Paper Element
Fuel Consumption @ Full Load	0.502 l/h
Fuel Consumption @ 3/4 Load	0.405 l/h
Fuel Consumption @ 1/2 Load	0.290 l/h
Decompression lever fitted (Yes / No)	Yes
Constant speed governor (Yes / No)	Yes
Constant speed	1500Rpm
Shut-down lever fitted (Yes / No)	Yes
Governor with 5% speed regulation fitted (Yes / No)	Yes
Pressure lubrication to crankshaft bearings (Yes / No)	Yes
Crank handle supplied (Yes / No)	Yes



