

**COMPONENTS 2005****(PTY) LTD****t/a ENGINE & HEAVY DUTY COMPONENTS****HEAD OFFICE JOHANNESBURG**

Tel: +27 (0)11 870 5000  
 Fax to Mail: 086 676 6628  
 Cnr Hubert & Marshall Streets,  
 Marshalltown, Johannesburg 2001  
 PO Box 6541 Johannesburg, 2000,  
 South Africa  
 ehd@ehd.co.za

**BLOEMFONTEIN**

Tel: +27 (0)51 430 5404  
 17 Krause Street, Oranjesig  
 PO Box 12471,  
 Brandhof, 9324  
 South Africa  
 ehdbloem@ehd.co.za

**CAPE TOWN**

Tel: +27 (0)21 510 0567  
 25 Bellray Business Park  
 Ampere Street, Stikland Industrial  
 Cape Town, 7530  
 PO Box 1037, Milnerton, 7435  
 South Africa  
 ehdcapetown@ehd.co.za

**DURBAN**

Tel: +27 (0)31 700 1160  
 Unit 3, Hillmax  
 31 Hillclimb Rd, Westmead 3610  
 PO Box 1054 Nagina 3604,  
 South Africa  
 ehd.dbn@ehd.co.za

**GAF1M9.5**

Model	GAF - 1M 9.5 KW
Rated sea-level power @ 1500 RPM	9.5 Kw (12.7395 Hp)
Derated power at 1500m ASL @ 1500 RPM	9.0 Kw (12.069 Hp)
Permissible working range	5.7 - 10.45 kW (7.6437-14.01345 Hp)
Number of Cylinders	Single
Bore / Stroke	114.3mm x 116.00mm
No. of strokes	Four
Type of Cooling	Air Cooling
Maximum Ambient Temperature for specified performance	45 C
Half speed PTO Shaft + rpm (Yes / No)	Yes (750 RPM)
Rotation of PTO Shaft (clockwise / anti-clockwise)	Clockwise seeing from Fly wheel
PTO Shaft suitable for V-belt drive (Yes / No)	Yes
Diameter and length of shaft + Stub shaft	38.1 mm Length 150 mm
Type of oil filter fitted	Cartridge Type (Paper Element)
Type of air cleaner fitted	Dry Type
Type of fuel filter fitted	Paper Element Type
Fuel Consumption @ Full Load	2.385 l/h
Fuel Consumption @ 3/4 Load	1.925 l/h
Fuel Consumption @ 1/2 Load	1.375 l/h
Decompression lever fitted (Yes / No)	Yes
Constant speed governor (Yes / No)	Yes
Constant speed	1500 RPM
Shut-down lever fitted (Yes / No)	Yes
Governor with 5% speed regulation fitted (Yes / No)	Yes
Pressure lubrication to crankshaft bearings (Yes / No)	Yes
Crank handle supplied (Yes / No)	Yes

**Proud Member of:**