

ehd

COMPONENTS 2005

(PTY) LTD

t/a ENGINE & HEAVY DUTY COMPONENTS

HEAD OFFICE JOHANNESBURG

Tel: +27 (0)11 870 5000
Fax to Mail: 086 676 6628
Cnr Hubert & Marshall Streets,
Marshalltown, Johannesburg 2001
ehd@ehd.co.za

BLOEMFONTEIN

Tel: +27 (0)51 430 5404
17 Krause Street, Oranjesig
South Africa
ehdbloem@ehd.co.za

CAPE TOWN

Tel: +27 (0)21 510 0567
25 Bellray Business Park
Ampere Street, Stikland Industrial
Cape Town, 7530
ehdcape@ehd.co.za

DURBAN

Tel: +27 (0)31 700 1160
Unit 3, Hillmax
31 Hillclimb Rd, Westmead 3610
ehddurban@ehd.co.za



Proud Member of:



Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers. Warranty conditions are available on our website www.ehd.co.za

4DX23-65D

Type	in line 4-cylinder 4-stroke
Air intake type	Turbo & Intercooling
Cooling mode	Water cooling
Governor mode	Mechanical or Electronic
Bore x Stroke (mm)	102 x 118
Compression ratio	17.1
Rated speed (rpm)	1500
Displacement (L)	3.86
Prime power (without fan)(kW)	48
Standby power (without fan)(kW)	53
Fuel consumption (L/h)	0.776
Oil consumption (L/h)	0.05
Steady state speed regulation (%)	<5
Oil capacity including filter (L)	13
Emission	Stage II
The flywheel shell interface	SAE3 Flywheel for 11.5" flexible coupling
Dry weight of base (kg)	380
Dry weight of Gen Pac (kg)	410
Overall dimension (base)(mm)	810 x 700 x 850
Overall dimension (G.P)(mm)	1480 x 705 x 900
Fan consumption (kW)	3
27°C air consumption (m ³ / min)	3.9
Heat rejection of exhaust (kW)	43.5
Exhaust gas temperature after turbine (°C)	480
Exhaust gas flow(m ³ / min)	10.4
Heat rejection from engine (kW)	3.3
Heat rejection of coolant (kW)	29
Base configuration	Standard configuration (add on the base)
Engine with fan	Intake and exhaust system: Air filter and connecting pipes
Alternator 500W 14V	Connecting flang of exhaust pipe
Starter motor 3.5kW 12V	Cooling system: Radiator with connecting pipes; Fan guard; Belt guard

Proud Member of:

