

HEAD OFFICE JOHANNESBURG Tel: +27 (0)11 870 5000 Fax to Mail: 086 676 6628 Cnr Hubert & Marshall Streets, Marshalltown, Johannesburg 2001 PO Box 6541 Johannesburg, 2000, South Africa ehd@ehd.co.za BLOEMFONTEIN Tel: +27 (0)51 430 5404 17 Krause Street, Oranjesig South Africa ehdbloem@ehd.co.za CAPE TOWN Tel: +27 (0)21 510 0567 25 Bellray Business Park Ampere Street, Stikland Industrial Cape Town, 7530 PO Box 1037, Milnerton, 7435 South Africa ehdcapetown@ehd.co.za

IOMPONENTS 2005

(PTY) LTD

t/a ENGINE & HEAVY DUTY COMPONENTS

DURBAN Tel: +27 (0)31 700 1160 Unit 3,Hillmax 31 Hillclimb Rd,Westmead 3610 PO Box 1054 Nagina 3604, South Africa ehddurban@ehd.co.za

GAF1HN

Model	GAF1
Rated sea-level power @ 1800 RPM	5.2 kW (7.1 Hp)
Derated power at 1500 m ASL @ 1500 RPM	4.5 kW (6.0345 Hp)
Permissible working range	2.7 - 4.95 kW (3.6207 - 6.63795 Hp)
Number of Cylinders	Single
Bore / Stroke	87.50 mm X 110.00 mm
No. of Strokes	Four
Type of Cooling	Air Cooling
Maximum Ambient Temperature for specified performance	45 C
Half speed PTO Shaft + rpm (Yes / No)	Yes (750RPM)
Rotation of PTO Shaft (clockwise / anti-clockwise)	Clockwise seeing from Fly wheel
PTO Shafts suitable for V-belt drive (Yes / No)	Yes
Diameter and length of shafts + stub shafts	38.1mm Length 150 mm
Type of Oil Filter Fitted	Cartridge Type (Paper Element)
Type of Air Cleaner Fitted	Dry Туре
Type of Fuel Filter Fitted	Paper Element
Fuel Consumption @ Full Load	1.130 l/h
Fuel Consumption @ 3/4 Load	0.915 l/h
Fuel Consumption @ 1/2 Load	0.650 l/h
Decompression level fitted (Yes / No)	Yes
Constant speed governor (Yes / No)	Yes
Constant speed	1500 RPM
Shut-down lever fitted (Yes / No)	Yes
Governor with 5% speed regulation fitted (Yes / No)	Yes
Pressure lubication to crankshaft bearings (Yes / No)	Yes
Crank handle supplied (Yes / No)	Yes

