


HEAD OFFICE JOHANNESBURG
 Tel: +27 (0)11 870 5000
 Fax to Mail: 086 676 6628
 Cnr Hubert & Marshall Streets,
 Marshalltown, Johannesburg 2001
 ehd@ehd.co.za

BLOEMFONTEIN
 Tel: +27 (0)51 430 5404
 17 Krause Street, Oranjesig
 Bloemfontein, 9301
 ehdbloem@ehd.co.za

CAPE TOWN
 Tel: +27 (0)21 510 0567
 25 Bellray Business Park
 Ampere Street, Stikland Industrial
 Cape Town, 7530
 ehdcapetown@ehd.co.za

DURBAN
 Tel: +27 (0)31 700 1160
 Unit 3, Hillmax
 31 Hillclimb Rd, Westmead 3610
 ehddurban@ehd.co.za



Co. Reg No. 2005/019759/07

Export Code. 20535466

Vat No. 4790223137

4DW93-42D

Type	in line 4-cylinder 4-stroke
Air intake type	Turbo & intercool
Cooling mode	Water cooling
Governor mode	Mechanical or Electronic
Bore x Stroke (mm)	90 x 100
Compression ratio	17.1
Rated speed (rpm)	1500
Displacement (L)	2.54
Prime power (without fan)(kW)	31
Standby power (without fan)(kW)	34
Fuel consumption (L/h)	0.762
Oil consumption (L/h)	0.04
Steady state speed regulation (%)	<5
Oil capacity including filter (L)	8
Emission	Stage II
The flywheel shell interface	SAE4 Flywheel for 7.5" & 10" flexible coupling
Dry weight of base (kg)	240
Dry weight of Gen Pac (kg)	280
Overall dimension (base)(mm)	750 x 600 x 735
Overall dimension (G.P)(mm)	1120 x 810 x 760
Fan consumption (kW)	2
27°C air consumption (m³ / min)	2.4
Heat rejection of exhaust (kW)	23.1
Exhaust gas temperature after turbine (°C)	450
Exhaust gas flow(m³ / min)	6.7
Heat rejection from engine (kW)	1.9
Heat rejection of coolant (kW)	17.1
Base configuration	Standard configuration (add on the base)
Engine with fan	Intake and exhaust system: Air filter and connecting pipes
Alternator 500W 14V	Connecting flang of exhaust pipe
Starter motor 3.5kW 12V	Cooling system: Radiator with connecting pipes; Fan guard; Belt guard

Proud Member of:

