

HEAD OFFICE JOHANNESBURG

Tel: +27 (0)11 870 5000

Fax to Mail: 086 676 6628

Cnr Hubert & Marshall Streets,

Marshalltown, Johannesburg 2001

ehd@ehd.co.za

BLOEMFONTEIN

Tel: +27 (0)51 430 5404

17 Krause Street, Oranjesig

Bloemfontein, 9301

ehdbloem@ehd.co.za

CAPE TOWN

Tel: +27 (0)21 510 0567

25 Bellray Business Park

Ampere Street, Stikland Industrial

Cape Town, 7530

ehdcapetown@ehd.co.za

DURBAN

Tel: +27 (0)31 700 1160

Unit 3, Hillmax

31 Hillclimb Rd, Westmead 3610

ehddurban@ehd.co.za

Co. Reg No. 2005/019759/07

Export Code. 20535466

Vat No. 4790223137

CA6DF2-19D



Engine Model	CA6DF2-19D
Type	6-Cylinder 4-Stroke
Air Intake Type	Turbo & Intercool
Cooling Type	Water Cooling
Governor Mode	Electron
Bore X Stroke (mm)	110 x 125
Compression Ratio	17:1
Rated Speed (rpm)	1500
Displacement (L)	7.12
Rated Power (without fan)(kW)	140
Standby Power (without fan)(kW)	154
Fuel Consumption (g/kWh)	200
Oil Consumption (L/h)	0.06
Steady State Speed Regulation (%)	<3
Oil Capacity Including Filter (L)	23
Emission Compliant	Stage II
The Flywheel Shell Interface	SAE2
	Flywheel for 11.5" Flexible Coupling
Dry Weight of Gen Pac (kg)	1000
Overall Dimension (st)(mm)	1386 x 680 x 1100
Fan Consumption (kW)	8
27C Air Consumption (m3/min)	12
Heat Rejection of Exhaust (kW)	120
Exhaust Gas Temperature After Turbine(C)	470
Exhaust Gas Flow (m3/min)	30
Heat Rejection From Engine (kW)	21
Heat Rejection of Coolant (kW)	81
Base Configuration	Standard Configuration (add on the base)
Engine with Fan	Intake and Exhaust System: Air filter and Connecting Pipes; Connecting Flang of Exhaust Pipe
Alternator 65A 28V Starter Motor 5kW 24V	Cooling System: Radiator; Connecting Pipes; Fan Guard; Belt Guard

Proud Member of:


Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers. Warranty conditions are available on our website www.ehd.co.za