

HEAD OFFICE JOHANNESBURG

Tel: +27 (0)11 870 5000

Fax to Mail: 086 676 6628

Cnr Hubert & Marshall Streets,
Marshalltown, Johannesburg 2001

ehd@ehd.co.za

BLOEMFONTEIN

Tel: +27 (0)51 430 5404

17 Krause Street, Oranjesig

Bloemfontein, 9301

ehdbloem@ehd.co.za

CAPE TOWN

Tel: +27 (0)21 510 0567

25 Bellray Business Park

Ampere Street, Stikland Industrial

Cape Town, 7530

ehdcape@ehd.co.za

DURBAN

Tel: +27 (0)31 700 1160

Unit 3, Hillmax

31 Hillclimb Rd, Westmead 3610

ehddurban@ehd.co.za

Co. Reg No. 2005/019759/07

Export Code. 20535466

Vat No. 4790223137

Model	GAF - 1M 2Kw
Rated sea-level power @ 1500 RPM	2.6 kW (3.4866 HP)
Derated power at 1500m ASL @ 1500 RPM	2.0 kW (2.682 Hp)
Permissible working range	1.2 - 2.2 kW(1.6092 - 2.9502 Hp)
Number of Cylinders	One
Bore / Stroke	80.00mm X 110.00mm
No. of strokes	Four
Type of Cooling	Air Cooling
Maximum Ambient Temperature for specified performance	45 C
Half speed PTO Shaft + rpm (Yes / No)	Yes (750RPM)
Rotation of PTO Shaft (clockwise / anti-clockwise)	Clockwise seeing from flywheel
PTO Shaft suitable for V-belt drive (Yes / No)	Yes
Diameter and length of shaft + Stub shaft	35.0 mm Length 150 mm
Type of oil filter fitted	Cartridge Type
Type of air cleaner fitted	Dry Type
Type of fuel filter fitted	Paper Element
Fuel Consumption @ Full Load	0.502 l/h
Fuel Consumption @ 3/4 Load	0.405 l/h
Fuel Consumption @ 1/2 Load	0.290 l/h
Decompression lever fitted (Yes / No)	Yes
Constant speed governor (Yes / No)	Yes
Constant speed	1500Rpm
Shut-down lever fitted (Yes / No)	Yes
Governor with 5% speed regulation fitted (Yes / No)	Yes
Pressure lubrication to crankshaft bearings (Yes / No)	Yes
Crank handle supplied (Yes / No)	Yes

Proud Member of:

