

HEAD OFFICE JOHANNESBURG

Tel: +27 (0)11 870 5000

Fax to Mail: 086 676 6628

Cnr Hubert & Marshall Streets,
Marshalltown, Johannesburg 2001

ehd@ehd.co.za

BLOEMFONTEIN

Tel: +27 (0)51 430 5404

17 Krause Street, Oranjesig

Bloemfontein, 9301

ehdbloem@ehd.co.za

CAPE TOWN

Tel: +27 (0)21 510 0567

25 Bellray Business Park

Ampere Street, Stikland Industrial

Cape Town, 7530

ehdcape@ehd.co.za

DURBAN

Tel: +27 (0)31 700 1160

Unit 3, Hillmax

31 Hillclimb Rd, Westmead 3610

ehddurban@ehd.co.za

Co. Reg No. 2005/019759/07

Export Code. 20535466

Vat No. 4790223137

Model	GAF – 2M 17Kw
Rated sea-level power @ 1500 RPM	18.25 Kw (24.47325 Hp)
Derated power at ± 1500 m ASL @ 1500 RPM	17.0 kW (22.797 Hp)
Permissible working range	10.2 - 18.7 kW (13.6782-25.0767 Hp)
Number of Cylinders	Two
Bore / Stroke	114.3 mm X 116 mm
No. of strokes	Four
Type of Cooling	Air Cooling
Maximum Ambient Temperature for specified performance	45 C
Half speed PTO Shaft + rpm (Yes / No)	Yes (750 RPM)
Rotation of PTO Shaft (clockwise / anti –clockwise)	Clockwise seeing from Fly wheel
PTO Shafts suitable for V-belt drive (Yes / No)	Yes
Diameter and length of shafts + Stub Shafts	38.1 mm Length 150 mm
Type of Oil Filter Fitted	Cartridge Type (Paper Element)
Type of Air Cleaner Fitted	Dry Type
Type of Fuel Filter Fitted	Paper Element Type
Fuel Consumption @ Full load	4.250 l/h
Fuel Consumption @ ¾ load	3.400 l/h
Fuel Consumption @ ½ load	2.450 l/h
Decompression lever fitted (Yes/No)	Yes
Constant speed governor (Yes/No)	Yes
Constant speed	1500 RPM
Shut-down lever fitted (Yes/No)	Yes
Governor with 5% speed regulation fitted (Yes/No)	Yes
Pressure lubrication to crankshaft bearings (Yes/No)	Yes
Crank handle supplied (Yes/No)	Yes

Proud Member of:



Manufacturer's names, numbers, symbols, photos and descriptions are used for reference purposes only and it is not implied that the parts referred to are the products of those manufacturers. Warranty conditions are available on our website www.ehd.co.za